




ASSY	ASSY QTY	B/O	Part #	UNIT	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG	٦ï	REF. AIRBUS T/N: M632V3015102.					
QIY	QIY	-, -		QTY	· ·		-,								
			-1	1	BODY	4140/4142		2	_	DARI					
			-3	1	GUIDE	4140/4142		3		AEROSPACE					
			-5	2	АТТАСН	6061		4		ALTERNATOR SEAL EXCHANGE			GF.		
			-7	1	HEX HEAD CAP SCREW	STEEL	M12 X 1.75mm (MCMASTER-CARR #91310A142) MODIFIED	5	L						
		B/O	-9	5	SOCKET HEAD CAP SCREW	STEEL	M5 X 0.8mm X 14mm (MCMASTER-CARR #95263A360)	1	1	RBEM632V3015102			REV 1		
		B/O	-11	1	WASHER	STEEL	M5 (MCMASTER-CARR #91100A140)	1	h	MAT'L UNLESS OTHERWISE SPECIFIED			PECIFIED		
		B/O	-13	1	WASHER	NYLON	M10 (MCMASTER-CARR #95610A600)	1					NSIONS ARE IN INCHES		
		B/O	-15	2	HEX HEAD CAP SCREW	STEEL	M10 X 1.5mm X 25mm (MCMASTER-CARR #91280A630)	1	F	FINISH			.XX ± .01	ANGLES :	
		B/O	-17	2	HEX NUT	STEEL	M10 X 1.5mm (MCMASTER-CARR #90591A171)	1	L	SPEC			1. BREAK A	L SHARP EDGES	1/
		B/O	-19	2	WASHER	STEEL	M10 (MCMASTER-CARR #91166A280)	1	_ L	DRAWN BY:	DUERFE			NAL LIMITS APPL	Y
		B/O	-21	1	ВОТТОМ ГОАМ	Y20 BLACK	2.08 X 6.04 X 10.54 (I.R. SPECIALTY)	6		CHECKED: OPPS APPR:	MACKO' ANDER			T DIM AND TOL P	ER
		B/O	-23	1	TOP FOAM	Y20 BLACK	1.08 X 6.04 X 10.54 (I.R. SPECAILTY)	7	ᆫ	QA APPR:	LINDSA		ASME Y14	USED ON MODE	L
		B/O	-25	1	CASE	PLASTIC	PELICAN #APP-1170-E	N/S	S A	APPROVED:	GILBER			H175	
		B/O		1	DART PLACARD	ALUMINUM	RB41011	N/S	S	SCALE	1:4	DATE	6/3/2016	SHEET 1	OF 7










RBEM632V3015102-3 MAT'L 4140/4142 UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .005 FRACTIONS ± 1/8 .XX + .01 ANGLES ±.5° .X ± .1 SURFACES = 125/ TREAT FINISH ZINC PLATE SPEC ASTM B633 TYPE I SC 2 1. BREAK ALL SHARP EDGES .015 x 45 'OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009 DRAWN BY: DUERFELDT CHECKED: MACKOVJAK OPPS APPR: ANDERSON QA APPR: USED ON MODEL LINDSAY APPROVED: GILBERT H175 SCALE 6/3/2016 SHEET 3 OF 7 1:1

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS								
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED			









ATTACH



"ALTERNATOR SEAL EXCHANGE


6/3/2016


SHEET 4 OF 7

Divo no.	RBEM632V3015102-5							
MAT'L 6061 HEAT TREAT		UNLESS OTHERWISE SPECIFIEI DIMENSIONS ARE IN INCHES .XXX ± .005 FRACTIONS ± 1/8						
FINISH POWD	ER COAT YELLOW	.XX ± .01 ANGLES ±.5° .X ± .1 SURFACES = 125						
SPEC FED#		1. BREAK ALL SHARP EDGES .015 x 45° OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING						
DRAWN BY:	DUERFELDT							
CHECKED:	MACKOVJAK							
OPPS APPR:	ANDERSON	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009						
QA APPR:	LINDSAY	USED ON MODEL						
APPROVED:	GILBERT	H175						

SCALE


1:1





DATE

INITIAL APPROVED



"ALTERNATOR SEAL EXCHANGE

RBEM632V3015102-7

2:1

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES

.XXX ± .005 FRACTIONS ± 1/8

.XX + .01 ANGLES ±.5°

.X ± .1 SURFACES = 125/

SHEET 5 OF 7

SPEC ASTM B633 TYPE I SC 2 1. BREAK ALL SHARP EDGES .015 x 45 'OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009 DUERFELDT MACKOVJAK ANDERSON

USED ON MODEL LINDSAY APPROVED: GILBERT H175 SCALE

6/3/2016

